

L6C-72

DIN Size W72 × H72mm


- 6 digits display with 7 segment LED display
- Seven output modes can be used in wide variety of applications
- Counting ranges from 0 to 999999
- Counting mode Up count or Down count selectable
- Memory function available




SPECIFICATIONS

MODEL		L6C-72
RATED VOLTAGE		12 ~ 60VDC/AC 50/60Hz 100 ~ 240VAC 50/60Hz
OPERATING VOLTAGE		85 ~ 110% of rated voltage
COUNTING RANGE		0~999999
CONTROL OUTPUT		Contact output 2C 7+11 Count input 7+12 Gate input 7+13 Reset input 7+14 Key protect input 7+6 DC12V output
CONTACT RATING		5A 250VAC Resistive Load
EXTERNAL RESET		○
EXTERNAL GATE		○
SELF-RESET		○
KEY PROTECT		○
MEMORY FUNCTION		○
12VDC OUTPUT		○
L I F E	MECHANICAL	5×10^6 times
	ELECTRICAL	10^5 times
RESET TIME		0.1 sec max
CONSUMED POWER		Max. 3VA
AMBIENT TEMPERATURE		-10°C ~ + 55°C
AMBIENT HUMIDITY		45 ~ 85%RH
WEIGHT		Approx. 197g


CONNECTION DIAGRAMS



TIMING CHARTS



DIMENSIONS



ANV ELECTRIC CO., LTD.

Kaohsiung Headquarter

No. 151, Jin Shan Road, Kaohsiung, Taiwan
Tel :+886 7 359 5833 Fax :+886 7 359 5822
E-Mail : anv@anv.com.tw

Taipei Office

No. 166, Fu Xing 3rd Street, Taishan Dist.,
New Taipei City, Taiwan
Tel :+886 2 2296 3133 Fax :+886 2 2296 3233
E-Mail : taipei@anv.com.tw

Tainan Office

No. 60, Lin Sen Road Sec. 1, Tainan, Taiwan
Tel:+886 6 216 0988 Fax:+886 6 216 0388
E-Mail : tainan@anv.com.tw

ANV ELECTRIC (HK) LTD

Flat 4, 14/F., Block 4, Wai Wah Centre,
Shatin, N.T., Hong Kong
Tel :+852 2690 2588 Fax :+852 2690 2511
E-Mail : anv@anv.com.hk

Taichung Office

No. 532, Wen Hsin Road Sec. 1, Taichung, Taiwan
Tel :+886 4 2320 9930 Fax :+886 4 2320 9960
E-Mail : taichung@anv.com.tw

ANV ELECTRIC (M) SDN. BHD

25-1, Jalan 1/116B, Kuchai Entrepreneur's Park,
Off Jalan Kuchai Lama, 58200 Kuala Lumpur, Malaysia
Tel :+60 3 7980 3328 Fax :+60 3 7980 3779
E-Mail : anv@anv.com.my